Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-673-2473

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
2.375 inches
Overall Height:
2.750 inches
Overall Width:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.188 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.188 inches
Distance From Mounting Shoulder To Front Face:
0.875 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
40-1 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi): 16 and 16 **Thread Size:** 2.250 inches and 2.500 inches **Terminal Location:** Back single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end all contact groupings **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Copper alloy **Included Contact Quantity:** 6 single mating end 2nd contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.054 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Uns and uns Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0