NSN 5935-00-677-9225

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-677-9225 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.903 inches **Overall Diameter:** Between 1.234 inches and 1.264 inches **Environmental Protection:** Moisture proof **Distance From Mounting Shoulder To Front Face:** Between 0.661 inches and 0.681 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.125 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 12-10 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 0.750 inches and 0.875 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-677-9225

No Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2

