Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-677-9229

# Thread Class:

2a and 2b

### **Thread Direction:**

Right-hand and right-hand

# Body Style:

Straight shape, internal coupling

#### **Overall Length:**

1.400 inches

#### **Overall Diameter:**

0.979 inches

#### **Environmental Protection:**

Moisture resistant

#### Threaded Device Type:

Back shell and coupling facility

#### Mating End Quantity:

1

# **Contact Position Arrangement Style:**

12-10 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

#### Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

#### **Polarization Method:**

Key, multiple key groove

#### **Insert Position In Deg:**

0.0

#### Shell Type:

Solid

## **Connector Locking Method:**

Internally threaded shell

## Thread Size:

0.750 inches and 0.750 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# NSN 5935-00-677-9229 Electrical Plug Connector - Page 2 of 2



	aterial:
	ingle mating end
Terminal	Туре:
Solder we	ell single mating end single contact grouping
Shell Ma	terial:
Aluminum	n alloy
Shell Su	rface Treatment:
Cadmium	I
Shell Su	rface Treatment Specification:
Qq-p-416	federal specification single treatment response
Included	Contact Quantity:
10 single	mating end single contact grouping
Included	Contact Type:
Round pi	n single mating end single contact grouping
Precious	Material And Location:
Contact s	urfaces gold and contact surfaces silver
Precious	Material And Weight:
0.010 gol	d grains, troy and 0.010 silver grains, troy
Precious	Material:
Gold and	silver
Thread S	eries Designator:
Unef and	unc
Shelf Life	ð:
N/a	
Unit Of N	leasure:
Demilitar	ization:
No	
Fiig:	
A039b0	