

View Online at <https://aerobasegroup.com/nsn/5935-00-681-1096>

Thread Class:

2b and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

2.438 inches

Overall Diameter:

2.719 inches

Environmental Protection:

Moisture resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

40-1 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

41.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

230.0

Shell Type:

Split

Connector Locking Method:

Internally threaded coupling nut

Thread Length:

0.500 inches and 0.625 inches

Thready Qty Per Inch (tpi):

16 and 16

Thread Size:

2.250 inches and 2.500 inches

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

6 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un and un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0