

View Online at <https://aerobasegroup.com/nsn/5935-00-681-3445>

Thread Class:

2a

Thread Direction:

Right-hand

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

7550.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

10600.0 single mating end single contact grouping

Connector Locking Method:

Latching ring

Thread Length:

0.250 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0