## NSN 5935-00-681-4368

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-681-4368 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.750 inches **Overall Diameter:** 0.875 inches **Distance From Mounting Shoulder To Front Face:** 1.500 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Rf single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Conduit nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 

0.562 inches and 0.562 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy

## NSN 5935-00-681-4368

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

**Thread Series Designator:** 

Unef and unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0