Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-681-4585

3.844 inches
Overall Height:
0.641 inches
Overall Width:
0.438 inches
Environmental Protection:
Vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.149 inches
Distance Between Mounting Facility Centers:
Between 1.711 inches and 1.725 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Turret single mating end single contact grouping
Contact Material Specification:
Qq-b-330, comp a federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 2 military specification single treatment response

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:** Mil-m-14, type mdg military specification single material response single mating end **Included Contact Quantity:** 14 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Special Features:** Polarized contact k **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.014 gold grains, troy and 0.014 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard):

Mil-m-14 spec.