

View Online at <https://aerobasegroup.com/nsn/5935-00-681-5620>

**Thread Direction:**

Right-hand

**Overall Length:**

1.125 inches

**Overall Height:**

0.875 inches

**Overall Width:**

0.875 inches

**Environmental Protection:**

Humidity resistant and weather resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.625 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.625 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Conduit nut

**Thread Size:**

0.625 inches

**Insert Material:**

Rubber synthetic single mating end

**Shell Material:**

Aluminum alloy

**Included Contact Quantity:**

3 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Polarized; 4 mtg holes; dim. Exclprotruding nylin follower

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0