Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-681-5793

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.359 inches
Overall Height:
Between 1.355 inches and 1.395 inches
Overall Width:
Between 1.355 inches and 1.395 inches
Environmental Protection:
Explosion proof and moisture proof and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.175 inches and 0.181 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.057 inches and 1.067 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.057 inches and 1.067 inches
Distance From Mounting Shoulder To Front Face:
Between 0.750 inches and 0.766 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-1 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
13.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end 1st contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end 1st contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid



## **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 14 **Thread Size:** 1.125 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Included Contact Quantity:** 6 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.010 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0

--