## NSN 5935-00-681-5892

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-681-5892 **Body Style:** Straight shape, flush mount **Overall Length:** 1.109 inches **Overall Height:** 1.688 inches **Overall Width:** 2.688 inches **Unthreaded Mounting Hole Diameter:** 0.144 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.188 inches **Mating End Quantity: Contact Position Arrangement Style:** 16 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 10.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 2350.0 single mating end 1st contact grouping Shell Type: Solid **Connector Locking Method:** Spring friction **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end all contact groupings **Insert Material:** Plastic melamine single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Anodize

## NSN 5935-00-681-5892

Electrical Receptacle Connector - Page 2 of 2



Included Contact Qua	ntity:
----------------------	--------

2 single mating end 1st contact grouping

**Included Contact Type:** 

Round pin single mating end 2nd contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.024 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A039b0