

View Online at <https://aerobasegroup.com/nsn/5935-00-682-0722>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape

**Overall Length:**

Between 0.922 inches and 0.954 inches

**Overall Height:**

Between 0.515 inches and 0.547 inches

**Overall Width:**

Between 0.265 inches and 0.297 inches

**Distance Between Mounting Facility Centers:**

Between 0.618 inches and 0.632 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

7 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**Thready Qty Per Inch (tpi):**

48 and 48 and 48

**Thread Size:**

0.099 inches and 0.099 inches and 0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Insert Material Specification:**

Mil-m-19833, ty gdi-30f military specification single material response single mating end

**Included Contact Quantity:**

7 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surface silver

**Precious Material And Weight:**

0.007 gold grains, troy and 0.007 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unc and unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-19833 spec.