NSN 5935-00-683-2132

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-683-2132

Thr	ead Class:
2a	
Thr	ead Direction:
Rigl	ht-hand
Boo	dy Style:
Stra	aight shape w/flange
Ονε	erall Length:
Betv	ween 2.011 inches and 2.026 inches
Ονε	erall Height:
Betv	ween 2.219 inches and 2.281 inches
Ονε	erall Width:
Betv	ween 2.219 inches and 2.281 inches
Unt	hreaded Mounting Hole Diameter:
Betv	ween 0.168 inches and 0.178 inches
Cen	nter To Center Distance Between Mounting Facilities Parallel To Height:
Betv	ween 1.745 inches and 1.755 inches
Dist	tance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Betv	ween 1.745 inches and 1.755 inches
Thr	eaded Device Type:
Cou	upling facility
Mat	ing End Quantity:
2	
Cor	ntact Position Arrangement Style:
32-7	7 all mating ends
Cor	ntact Removability:
Non	nremovable all mating ends all contact groupings
Cor	ntact Maximum Current Rating In Amps:
23.0	0 2nd mating end 2nd contact grouping
Cor	ntact Maximum Ac Voltage Rating In Volts:
500	.0 1st mating end 2nd contact grouping
Cor	ntact Maximum Dc Voltage Rating In Volts:
700	.0 2nd mating end 3rd contact grouping
Pola	arization Method:
Key	v, multiple key groove
Inse	ert Position In Deg:
280	.0 and 80.0
She	ell Type:
Soli	d
Cor	nnector Locking Method:
Exte	ernally threaded shell
Thr	ead Length:
0.62	25 inches

NSN 5935-00-683-2132

Connector Adapter - Page 2 of 2

18



Thready Qty Per Inch (tpi): **Thread Size:** 2.000 inches **Contact Material:** Copper alloy all mating ends all contact groupings **Contact Surface Treatment:** Gold all mating ends all contact groupings and silver all mating ends all contact groupings **Insert Material:** Rubber all mating ends Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Shell Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Included Contact Quantity:** 7 2nd mating end 2nd contact grouping **Included Contact Type:** Round socket 2nd mating end all contact groupings **Precious Material And Location:** Contact surface gold and contact surface silver **Precious Material And Weight:** 0.070 gold grains, troy and 0.070 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-a-8625 spec.