

View Online at <https://aerobasegroup.com/nsn/5935-00-683-4945>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape

Overall Length:

1.344 inches

Overall Diameter:

0.562 inches

Distance From Mounting Shoulder To Front Face:

0.579 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd 1st mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Bayonet latch and externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thready Qty Per Inch (tpi):

32 and 32

Thread Size:

0.190 inches and 0.375 inches

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene single mating end

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

2 all mating ends all contact groupings

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin all mating ends all contact groupings

Precious Material And Location:

Contact surface silver and shell surface silver

Precious Material:

Silver

Thread Series Designator:

Unf and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0