NSN 5935-00-683-5156

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-683-5156 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.984 inches **Overall Height:** Between 1.261 inches and 1.301 inches **Overall Width:** Between 1.261 inches and 1.301 inches **Environmental Protection:** Explosion proof and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.148 inches and 0.154 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.964 inches and 0.974 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.964 inches and 0.974 inches **Distance From Mounting Shoulder To Front Face:** Between 0.562 inches and 0.578 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16s-6 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

NSN 5935-00-683-5156

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.391 inches
Thready Qty Per Inch (tpi):
10
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0