
## NSN 5935-00-683-5978

Tip Jack - Page 1 of 2

**Thread Class:** 





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Violet **Body Style:** Threaded bushing mounted **Overall Length:** 0.906 inches Mounting Bushing Length: 0.563 inches **Body Length:** 0.751 inches **Overall Diameter:** 0.375 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 11000.0 dc Accommodated Finger Type: Banana spring single finger **Finger Accommodation Diameter:** 0.175 inches single finger Finger Accommodation Length: 0.531 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches Capacitance In Picofarads: 2.0 **Current Rating In Amps:** 10.0 Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug Material: Plastic insulator

# NSN 5935-00-683-5978

Tip Jack - Page 2 of 2

Material:

Plastic insulator

Precious Material And Location:

Termnal surface silver

Precious Material:

Silver

### Surface Treatment:

Silver terminal

### Surface Treatment:

Silver terminal

#### **Thread Series Designator:**

Unef

Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

#### Fiig:

A03400

