
## NSN 5935-00-683-7651

Tip Jack - Page 1 of 2

**Thread Class:** 





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 1.031 inches Mounting Bushing Length: 0.563 inches **Body Length:** 0.750 inches **Overall Diameter:** 0.375 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 9000.0 dc Accommodated Finger Type: Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger Finger Accommodation Length: 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.266 inches **Capacitance In Picofarads:** 2.0 **Current Rating In Amps:** 10.0 Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug Material: Plastic, polyamide insulator

## NSN 5935-00-683-7651

Tip Jack - Page 2 of 2

Material:

Unit Of Measure:

Demilitarization:

---

No **Fiig:** A03400

Plastic polyamide insulator Precious Material And Location: Contact spring surface silver Precious Material: Silver Surface Treatment: Silver spring Surface Treatment: Silver spring Thread Series Designator: Unef Shelf Life: N/a

