

View Online at <https://aerobasegroup.com/nsn/5935-00-683-7774>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

Between 2.047 inches and 2.141 inches

**Overall Diameter:**

Between 1.031 inches and 1.062 inches

**Cable Entrance Diameter:**

Between 0.516 inches and 0.547 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Wk-6 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1300.0 single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Connector Cable Strain Relief Method:**

Cable clamp

**Thready Qty Per Inch (tpi):**

6

**Thread Size:**

0.875 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic melamine single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

6 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.006 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0