NSN 5935-00-685-9396

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-685-9396 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** White **Body Style:** Threaded bushing mounted **Overall Length:** 1.000 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.500 inches **Overall Diameter:** 0.406 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 2000.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.563 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Current Rating In Amps:** Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.250 inches **Terminal Type:** Turret Material: Plastic insulator

Material:Plastic insulator

NSN 5935-00-685-9396 Tip Jack - Page 2 of 2



Precious Material And Location:
Contact spring surface gold
Precious Material:
Gold
Surface Treatment:
Gold spring
Surface Treatment:
Gold spring
Test Data Document:
96906-ms-16108 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Jnef
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
\ 03400