NSN 5935-00-686-3013

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-686-3013 **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 0.750 inches and 0.780 inches **Overall Height:** Between 1.328 inches and 1.358 inches **Overall Width:** Between 1.328 inches and 1.358 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.057 inches and 1.067 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.057 inches and 1.067 inches **Distance From Mounting Shoulder To Front Face:** Between 0.454 inches and 0.484 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 6 **Thread Size: 1.312** inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-00-686-3013

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
6 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0