NSN 5935-00-686-3225

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-686-3225

Thr	ead Class:
2a	
Boo	dy Style:
Stra	ight shape w/flange
Ove	erall Length:
2.02	20 inches
Ονε	erall Height:
Betv	ween 1.594 inches and 1.656 inches
Ove	erall Width:
Betv	ween 1.594 inches and 1.656 inches
Unt	hreaded Mounting Hole Diameter:
Bet	ween 0.115 inches and 0.130 inches
Cer	nter To Center Distance Between Mounting Facilities Parallel To Height:
Bet	ween 1.245 inches and 1.255 inches
Dis	tance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Bet	ween 1.245 inches and 1.255 inches
Dis	tance From Mounting Shoulder To Front Face:
Bet	ween 0.750 inches and 0.781 inches
Thr	eaded Device Type:
Οοι	upling facility
Mat	ing End Quantity:
2	
Cor	ntact Removability:
Nor	nremovable all mating ends all contact groupings
Cor	ntact Maximum Current Rating In Amps:
73.0) all mating ends all contact groupings
Cor	ntact Maximum Ac Voltage Rating In Volts:
900	.0 all mating ends all contact groupings
Cor	ntact Maximum Dc Voltage Rating In Volts:
125	0.0 all mating ends all contact groupings
Pol	arization Method:
Key	r, multiple key groove
Inse	ert Position In Deg:
0.0	
She	ell Type:
Soli	d
Cor	nnector Locking Method:
Exte	ernally threaded shell
Inse	ert Material:
Plas	stic all mating ends
She	ell Material:
Alur	minum alloy

NSN 5935-00-686-3225

Connector Adapter - Page 2 of 2



Included Contact Quantity:

3 all mating ends all contact groupings

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0