NSN 5935-00-686-3633

Thread Class:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-686-3633

2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.437 inches
Overall Diameter:
1.125 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14s-9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
0.0 Shell Type:
•
Shell Type:
Shell Type: Solid
Shell Type: Solid Connector Locking Method:
Shell Type: Solid Connector Locking Method: Externally threaded shell
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size:
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location:
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Insert Material:
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type:
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Shell Type: Solid Connector Locking Method: Externally threaded shell Thread Size: 0.750 inches Terminal Location: Back single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate

Round socket single mating end single contact grouping

NSN 5935-00-686-3633

Electrical Plug Connector - Page 2 of 2



Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0