Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-686-3640

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, flange moun	t external coupling
Overall Length:	, one national operations
1.406 inches	
Overall Height:	
Between 1.015 inches and 1.	.047 inches
Overall Width:	
Between 1.015 inches and 1.	.047 inches
Environmental Protection:	
Moisture proof	
Unthreaded Mounting Hole	Diameter:
Between 0.115 inches and 0.	
Center To Center Distance	Between Mounting Facilities Parallel To Height:
Between 0.807 inches and 0.	
Distance Between Centerlin	nes Of Mounting Facilities Parallel To Body Width:
Between 0.807 inches and 0.	817 inches
Cable Entrance Diameter:	
0.548 inches	
Distance From Mounting S	houlder To Front Face:
Between 0.406 inches and 0.	416 inches
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangem	ent Style:
12-10 single mating end	
Contact Removability:	
Nonremovable single mating	end single contact grouping
Contact Maximum Current	Rating In Amps:
7.5 single mating end single	contact grouping
Contact Maximum Ac Volta	ge Rating In Volts:
500.0 single mating end sing	le contact grouping
Contact Maximum Dc Volta	ge Rating In Volts:
700.0 single mating end sing	le contact grouping
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
0.0	

Electrical Receptacle Connector - Page 2 of 2



Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): 10 **Thread Size:** 0.750 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 10 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.010 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Double stub Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig:

A039b0