Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-686-3989

Thread Class:
2b Thread Pitch Diameters:
+1.000/+1.008 inches
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 0.719 inches and 0.749 inches
Overall Diameter:
Between 1.157 inches and 1.187 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16-3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
3000.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Thready Qty Per Inch (tpi):
6
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping

## NSN 5935-00-686-3989 Electrical Plug Connector - Page 2 of 2



Plastic mela	mine single mating end
Terminal Ty	
۔ Solder well s	- single mating end single contact grouping
Shell Materi	al:
Aluminum al	loy
Shell Surfac	ce Treatment:
Cadmium	
Insert Mate	ial Specification:
Mil-m-14, typ	be mme military specification single material response single mating end
Included Co	ontact Quantity:
3 single mat	ing end single contact grouping
Included Co	ontact Type:
Round pin si	ngle mating end single contact grouping
Precious Ma	aterial And Location:
Contact surf	aces gold and contact surfaces silver
Precious Ma	aterial And Weight:
0.003 gold g	rains, troy and 0.003 silver grains, troy
Precious Ma	aterial:
Gold and silv	/er
Thread Seri	es Designator:
Acme	
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	tion:
No	
Fiig:	
A039b0	
Mil-std (mili	tary Standard):
Mil-m-14 spe	ec.