Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-686-9258

| Thread Direction: |
|---|
| Right-hand |
| Overall Length: |
| 0.828 inches |
| Overall Height: |
| 0.812 inches |
| Overall Width: |
| 0.812 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.625 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.625 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Maximum Current Rating In Amps: |
| 22.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 700.0 single mating end single contact grouping |
| Connector Locking Method: |
| Externally threaded shell |
| Thread Size: |
| 0.625 inches |
| Insert Material: |
| Plastic single mating end |
| Shell Material: |
| Aluminum alloy |
| Included Contact Quantity: |
| 2 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Polarized |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0