NSN 5935-00-686-9382

Body Style:

Overall Length:

Straight shape, flush mount

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-686-9382

1.687 inches
Overall Height:
1.850 inches
Overall Width:
3.375 inches
Unthreaded Mounting Hole Diameter:
0.150 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.875 inches
Distance From Mounting Shoulder To Front Face:
0.062 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
A45 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
30.0 single mating end 1st contact grouping
Polarization Method:
Contact
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end all contact groupings
Terminal Type:
Solder well single mating end all contact groupings

NSN 5935-00-686-9382

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Included Contact Quantity:
43 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.045 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.