NSN 5935-00-687-0244

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-687-0244

Overall Length:
1.656 inches
Overall Diameter:
0.734 inches
Environmental Protection:
Moisture resistant
Cable Entrance Diameter:
0.250 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
8-4 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Delevineties Methods
Polarization Method:
Keyway or multiple keyway
Keyway or multiple keyway
Keyway or multiple keyway Insert Position In Deg:
Keyway or multiple keyway Insert Position In Deg: 0.0
Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid
Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method:
Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch
Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method:
Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Insert Material:
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Insert Material: Rubber single mating end
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Insert Material: Rubber single mating end Terminal Type:
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Insert Material: Rubber single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:

Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-00-687-0244

Electrical Plug Connector - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0