## NSN 5935-00-687-1886

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-687-1886

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

2.531 inches

**Overall Height:** 

0.875 inches

**Overall Width:** 

0.375 inches

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

**Distance Between Mounting Facility Centers:** 

2.156 inches

**Board Accommodated Length:** 

1.727 inches single board

**Board Accommodated Width:** 

0.062 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Bridged contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic phenolic single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type mfh military specification single material response single mating end

**Included Contact Quantity:** 

10 single mating end single contact grouping

**Included Contact Type:** 

Leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

## NSN 5935-00-687-1886

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.010 gold grains, troy and 0.010 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039h0

Mil-std (military Standard):

Mil-m-14 spec.