

View Online at <https://aerobasegroup.com/nsn/5935-00-687-1891>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle, shape, internal coupling

**Overall Length:**

0.780 inches

**Overall Height:**

0.760 inches

**Overall Diameter:**

0.343 inches

**Environmental Protection:**

Watertight

**Cable Entrance Diameter:**

0.140 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Connector Cable Strain Relief Method:**

Cable clamp

**Thread Size:**

0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-f-14072 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Surface Treatment Specification:**

Mil-f-14072 federal specification single treatment response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces and body surface silver

**Precious Material And Weight:**

0.105 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-f-14072 spec.