## NSN 5935-00-687-1976

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-687-1976 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, flange mount **Overall Length:** 1.312 inches **Bushing Diameter:** 0.969 inches **Overall Height:** 1.219 inches **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 85.0 Shell Type: Solid **Connector Locking Method:** Bayonet shell **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-00-687-1976

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Copper
Included Contact Quantity:
26 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0