NSN 5935-00-687-2150

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-687-2150

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.750 inches
Overall Height:
0.680 inches
Overall Width:
0.610 inches
Distance Between Mounting Facility Centers:
1.417 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
,
Nonremovable single mating end single contact grouping
·
Nonremovable single mating end single contact grouping
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Mating end
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Mating end Shell Type:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Thready Qty Per Inch (tpi):
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Thready Qty Per Inch (tpi): 48
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Thready Qty Per Inch (tpi): 48 Thread Size:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Thready Qty Per Inch (tpi): 48 Thread Size: 0.099 inches
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Thready Qty Per Inch (tpi): 48 Thread Size: 0.099 inches Terminal Location:

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

NSN 5935-00-687-2150

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-b-613, comp 2 federal specification single material response
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.