NSN 5935-00-688-3531

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-688-3531 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 1.000 inches **Overall Height:** 0.906 inches **Overall Width:** 1.000 inches **Environmental Protection:** Moisture resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.719 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.719 inches **Cable Entrance Diameter:** 0.609 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Insert Material:** Plastic single mating end **Included Contact Quantity:** 2 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-00-688-3531

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Polarized
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0