Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-688-3704

2a         Thread Direction:         Right-hand         Body Style:         Straight shape threaded         Overall Length:         1.407 inches         Overall Diameter:         2.125 inches         Distance From Mounting Shoulder To Front Face:         1.219 inches         Mounting Facility Thickness:         Between 0.094 inches and 0.312 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Removability:         Norremovable single mating end single contact grouping         Polarization Method:         Keyway or multiple keyway         Bother Tocking Method:         Norremovable single mating end single contact grouping         Onector Locking Method:         Norread Length:         0.0         Solid         Connector Locking Method:         Internally threaded shell         Thread Length:         0.734 inches         Thread Size:         1.625 inches         Etriminal Location:         Back single mating end single contact grouping         Corpear alloy single mating end single contact grouping
Right-hand         Body Style:         Straight shape threaded         Overall Length:         1.407 inches         Overall Diameter:         2.125 inches         Distance From Mounting Shoulder To Front Face:         1.219 inches         Mounting Facility Thickness:         Between 0.094 inches and 0.312 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Concatc Removability:         Nonremovable single mating end single contact grouping         Polization Method:         Keyway or multiple keyway         Insert Position In Deg:         0.0         Shell Type:         Solid         Connector Locking Method:         Internally threaded shell         Thread Length:         0.734 inches         Thread Size:         1.625 inches         Terminal Location:         Back single mating end single contact grouping         Cinact Material:
Body Style:         Straight shape threaded         Overall Length:         1.407 inches         Overal Diameter:         2.125 inches         Distance From Mounting Shoulder To Front Face:         1.219 inches         Mounting Facility Thickness:         Between 0.094 inches and 0.312 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Concat Removability:         Nonremovable single mating end single contact grouping         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         0.0         Shell Type:         Solid         Connector Locking Method:         Internally threaded shell         Thread Length:         0.734 inches         Thread Size:         1.625 inches         Thread Size:         1.625 inches         Terminal Location:         Back single mating end single contact grouping         Contact Material:
Straight shape threadedOverall Length:1.407 inchesOverall Diameter:2.125 inchesDistance From Mounting Shoulder To Front Face:1.219 inchesMounting Facility Thickness:Between 0.094 inches and 0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded shellThreade Length:0.734 inchesThread Size:1.625 inchesThread Size:1.625 inchesContact Material:Copper alloy single mating end single contact grouping
Overall Length:1.407 inchesOverall Diameter:2.125 inchesDistance From Mounting Shoulder To Front Face:1.219 inchesMounting Facility Thickness:Between 0.094 inches and 0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded shellThread Length:0.734 inchesThread Size:1.625 inchesTerminal Location:Back single mating end single contact groupingContact Kemovability:SolidContact Locking Method:Internally threaded shellThread Length:0.734 inchesThread Size:1.625 inchesTerminal Location:Back single mating end single contact groupingContact Materiai:Copper alloy single mating end single contact grouping
<ul> <li>1.407 inches</li> <li>Overall Diameter:</li> <li>2.125 inches</li> <li>Distance From Mounting Shoulder To Front Face:</li> <li>1.219 inches</li> <li>Mounting Facility Thickness:</li> <li>Between 0.094 inches and 0.312 inches</li> <li>Threaded Device Type:</li> <li>Coupling facility</li> <li>Mating End Quantity:</li> <li>Ating End Quantity:</li> <li>Nonremovable single mating end single contact grouping</li> <li>Polarization Method:</li> <li>Keyway or multiple keyway</li> <li>Insert Position In Deg:</li> <li>0.0</li> <li>Shell Type:</li> <li>Solid</li> <li>Connector Locking Method:</li> <li>Internally threaded shell</li> <li>Thread Length:</li> <li>0.734 inches</li> <li>Thread Size:</li> <li>1.625 inches</li> <li>Terminal Location:</li> <li>Back single mating end single contact grouping</li> <li>Contact Material:</li> <li>Contact Material:</li> <li>Copper alloy single mating end single contact grouping</li> </ul>
Overall Diameter:2.125 inchesDistance From Mounting Shoulder To Front Face:1.219 inchesMounting Facility Thickness:Between 0.094 inches and 0.312 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:0.0SolidConnector Locking Method:Internally threaded shellThread Length:0.734 inchesThread Size:1.625 inchesTerminal Location:Back single mating end single contact groupingContact Material:Contact Material:Contact Removabile in the policie in th
2.125 inches 2.125 inches Distance From Mounting Shoulder To Front Face: 1.219 inches Mounting Facility Thickness: Between 0.094 inches and 0.312 inches Threaded Device Type: Coupling facility Mating End Quantity: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded shell Thread Length: 0.734 inches Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Conper alloy single mating end single contact grouping Contact Material:
Distance From Mounting Shoulder To Front Face: 1.219 inches Mounting Facility Thickness: Between 0.094 inches and 0.312 inches Threaded Device Type: Coupling facility Mating End Quantity: Coupling facility Mating End Quantity: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded shell Thread Length: 0.734 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material:
1.219 inches         Mounting Facility Thickness:         Between 0.094 inches and 0.312 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         0.0         Shell Type:         Solid         Connector Locking Method:         Internally threaded shell         Thread Length:         0.734 inches         Thread Size:         1.625 inches         Terminal Location:         Back single mating end single contact grouping         Contact Material:
Mounting Facility Thickness:         Between 0.094 inches and 0.312 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         0.0         Shell Type:         Solid         Connector Locking Method:         Internally threaded shell         Thready Qty Per Inch (tpi):         18         Thread Size:         1.625 inches         Terminal Location:         Back single mating end single contact grouping         Contact Material:
Between 0.094 inches and 0.312 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         0.0         Shell Type:         Solid         Connector Locking Method:         Internally threaded shell         Thread Length:         0.734 inches         Thread Size:         1.625 inches         Terminal Location:         Back single mating end single contact grouping         Copper alloy single mating end single contact grouping         Insert Material:
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded shell Thread Length: 0.734 inches Thread Juper Inch (tpi): 18 Thread Size: 1.625 inches Thread Size: 1.625 inches Cornact Material: Copper alloy single mating end single contact grouping Contact Material:
Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded shell Thread Length: 0.734 inches Thread Size: 1.625 inches Thread Size: 1.625 inches Eack single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         0.0         Shell Type:         Solid         Connector Locking Method:         Internally threaded shell         Thread Length:         0.734 inches         Thready Qty Per Inch (tpi):         18         Thread Size:         1.625 inches         Terminal Location:         Back single mating end single contact grouping         Contact Material:
1         Contact Removability:         Nonremovable single mating end single contact grouping         Polarization Method:         Keyway or multiple keyway         Insert Position In Deg:         0.0         Shell Type:         Solid         Connector Locking Method:         Internally threaded shell         Thread Length:         0.734 inches         Thready Qty Per Inch (tpi):         18         Thread Size:         1.625 inches         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping
Contact Removability:Nonremovable single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded shellThread Length:0.734 inchesThread Size:1.625 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingInsert Material:
Nonremovable single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded shellThread Length:0.734 inchesThread Y Per Inch (tpi):18Thread Size:1.625 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact grouping
Polarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded shellThread Length:0.734 inchesThready Qty Per Inch (tpi):18Thread Size:1.625 inchesTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingInsert Material:
Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded shellThread Length:0.734 inchesThready Qty Per Inch (tpi):18Thread Size:1.625 inchesTerminal Location:Back single mating end single contact groupingCopper alloy single mating end single contact groupingInsert Material:
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded shell Thread Length: 0.734 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
0.0 Shell Type: Solid Connector Locking Method: Internally threaded shell Thread Length: 0.734 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Shell Type:   Solid   Connector Locking Method:   Internally threaded shell   Thread Length:   0.734 inches   Thready Qty Per Inch (tpi):   18   Thread Size:   1.625 inches   Terminal Location:   Back single mating end single contact grouping   Contact Material:   Copper alloy single mating end single contact grouping
Solid Connector Locking Method: Internally threaded shell Thread Length: 0.734 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Internally threaded shell Thread Length: 0.734 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Internally threaded shell Thread Length: 0.734 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
Thread Length: 0.734 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
0.734 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
Thready Qty Per Inch (tpi): 18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
18 Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Insert Material:
Contact Material: Copper alloy single mating end single contact grouping Insert Material:
Copper alloy single mating end single contact grouping Insert Material:
Insert Material:
Plastic single mating end
5 5
Terminal Type:
Solder well single mating end single contact grouping



**Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize Included Contact Quantity: 4 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round keyed **Included Contact Type:** Round pin single mating end single contact grouping **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0