NSN 5935-00-689-1200

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-689-1200

| Thread Class: |
|--|
| 2a and 2b and 2a |
| Thread Direction: |
| Right-hand and right-hand and right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 2.750 inches |
| Overall Height: |
| 0.656 inches |
| Overall Width: |
| 1.531 inches |
| Environmental Protection: |
| Moisture resistant and shock resistant and vibration resistant |
| Distance Between Mounting Facility Centers: |
| 2.375 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 25-104 single mating end |
| Polarization Method: |
| Jackscrew and shell |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Thready Qty Per Inch (tpi): |
| 32 and 32 and 32 |
| Thread Size: |
| 0.138 inches and 0.138 inches and 0.164 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Insert Material Specification: |
| Mil-m-14, ty sdg-f military specification single material response single mating end |
| Shell Guide Type And Location Designator: |

C slot

NSN 5935-00-689-1200

Electrical Receptacle Connector Body - Page 2 of 2



| Thread Series Designator: |
|--------------------------------|
| Unc and unc and unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |
| Demilitarization: |
| Demilitarization: No |
| |

Mil-std (military Standard):

Mil-m-14 spec.