Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-689-1255

## **Body Style:**

Straight edge type w/mounting flange

**Overall Length:** 

3.268 inches

## **Overall Height:**

0.660 inches

## **Overall Width:**

Between 0.325 inches and 0.345 inches

## **Unthreaded Mounting Hole Diameter:**

0.125 inches

#### **Distance Between Mounting Facility Centers:**

Between 2.931 inches and 2.945 inches

#### **Board Accommodated Length:**

2.498 inches single board and 2.510 inches single board

## **Board Accommodated Width:**

0.063 inches

## Mating End Quantity:

1

## Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

#### **Polarization Method:**

Contact to contact polarizing keys

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Tab, solder lug single mating end single contact grouping

# Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

# Included Contact Quantity:

15 single mating end single contact grouping



## Included Contact Type:

Bifurcated accordian leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.015 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.