## NSN 5935-00-689-1273

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-689-1273

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape threaded

**Overall Length:** 

Between 1.639 inches and 1.643 inches

**Overall Diameter:** 

Between 2.873 inches and 2.877 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant and watertight

**Distance From Mounting Shoulder To Front Face:** 

1.329 inches

**Mounting Facility Thickness:** 

Between 0.094 inches and 0.328 inches

**Threaded Device Type:** 

Coupling facility and mounting bushing

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

32-73 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

20.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

Thready Qty Per Inch (tpi):

16 and 16

**Thread Size:** 

2.375 inches and 2.375 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

## NSN 5935-00-689-1273

Electrical Receptacle Connector - Page 2 of 2



| Contact Surface Treatment:  |
|---|
| Gold single mating end single contact grouping  |
| Insert Material:  |
| Plastic single mating end   |
| Contact Surface Treatment Specification:  |
| Qq-s-365, type 2, grade a federal specification single treatment response single mating end single contact grouping |
| Terminal Type:  |
| Solder well single mating end single contact grouping   |
| Shell Material:   |
| Aluminum alloy  |
| Shell Surface Treatment:  |
| Cadmium   |
| Included Contact Quantity:  |
| 46 single mating end single contact grouping  |
| Bushing Accommodation Hole Shape:   |
| Round   |
| Included Contact Type:  |
| Round pin single mating end single contact grouping   |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.046 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Thread Series Designator:   |
| Un and un   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
|   |