# NSN 5935-00-689-1939

Electrical Plug Connector - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5935-00-669-1959
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
2.219 inches
Overall Diameter:
1.484 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Cable Entrance Diameter:
0.750 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37-2p single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
25.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
25.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:

Cadmium

## NSN 5935-00-689-1939

Electrical Plug Connector - Page 2 of 2



### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

### **Included Contact Quantity:**

24 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.024 gold grains, troy and 0.024 silver grains, troy

#### **Precious Material:**

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

\_\_

Demilitarization:

No

Fiig:

A039b0