

View Online at https://aerobasegroup.com/nsn/5935-00-689-4515

Thread Class:2b and 2b2b and 2aThread Direction:Right-hand and right-handBody Style:Rectangular shape center screwlockOverall Length:Between 4.118 inches and 4.138 inches	
Thread Direction: Right-hand and right-hand Body Style: Rectangular shape center screwlock Overall Length:	
Right-hand and right-hand Body Style: Rectangular shape center screwlock Overall Length:	
Body Style: Rectangular shape center screwlock Overall Length:	
Rectangular shape center screwlock Overall Length:	
Overall Length:	
-	
Between 4.118 inches and 4.138 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
Between 3.798 inches and 3.818 inches	
Overall Height:	
0.834 inches	
Overall Width:	
Between 0.687 inches and 0.707 inches	
Unthreaded Mounting Hole Diameter:	
0.125 inches	
Threaded Device Type:	
Coupling facility and back shell	
Mating End Quantity:	
15	
Contact Position Arrangement Style:	
244 single mating end	
Polarization Method:	
Polarization boss and jackscrew	
Connector Locking Method:	
Post jacksocket	
Thread Size:	
0.138 inches and 0.138 inches and 0.164 inches	
Insert Material:	
Plastic diallyl phthalate single mating end and silicon single mating end	
Insert Material Specification:	
Mil-p-19833, type gdi-30f military specification single material response single mating end or mil-m-14, ty sdg-f military specification	fication single
material response single mating end	
Thread Series Designator:	
Unc and unef	
Specification Data:	
06481-903017 manufacturers source control	
Shelf Life:	
N/a	
Unit Of Measure:	



Fiig: A039b0

Mil-std (military Standard):

Mil-p-19833 spec.