

View Online at <https://aerobasegroup.com/nsn/5935-00-689-4683>

**Body Style:**

Angle, shape, internal coupling

**Overall Diameter:**

Between 0.525 inches and 0.565 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Cable Entrance Diameter:**

Between 0.133 inches and 0.173 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Crimp type

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Surface Treatment Specification:**

Qq-s-365 federal specification single treatment response

**Shell Material Specification:**

Qq-b-626, comp 22 federal specification single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold and shell surface silver

**Precious Material And Weight:**

0.005 gold grains, troy and 0.100 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0