NSN 5935-00-689-6829

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-689-6829 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 2.635 inches and 2.645 inches **Overall Height:** 0.844 inches **Overall Width:** Between 0.431 inches and 0.441 inches **Distance Between Mounting Facility Centers:** Between 2.305 inches and 2.320 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 41 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Wire wrap single mating end single contact grouping **Included Contact Quantity:**

Included Contact Type:

Round socket single mating end single contact grouping

31 single mating end single contact grouping

NSN 5935-00-689-6829

Electrical Receptacle Connector - Page 2 of 2



Special Features: Contacts a, b, c, j, r, d, m, r, u, w omitted Precious Material And Location: Contact surfaces gold and contact surfaces silver Precious Material And Weight: 0.031 gold grains, troy and 0.031 silver grains, troy Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A039b0