NSN 5935-00-689-7334

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-689-7334 **Body Style:** Straight shape **Overall Length:** 1.750 inches **Overall Height:** 0.711 inches **Overall Width:** 0.610 inches **Unthreaded Mounting Hole Diameter:** 0.099 inches **Distance Between Mounting Facility Centers:** 1.417 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Cadmium single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Criticality Code Justification:** Feat **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy

Chromate

Shell Surface Treatment:

NSN 5935-00-689-7334

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, type mdg military specification single material response single mating end

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. L00672

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.