Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-690-0460

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
2.406 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.000 inches
Overall Height:
0.921 inches
Overall Width:
1.000 inches
Environmental Protection:
Corrosion resistant and moisture resistant and vibration resistant
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.562 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
21 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



	ace Treatment:
	nating end single contact grouping
Insert Materi	al:
Plastic diallyl	phthalate single mating end
Contact Surf	ace Treatment Specification:
Mil-g-45204 n	nilitary specification single treatment response single mating end single contact groupin
Terminal Typ	be:
Solder well si	ngle mating end single contact grouping
Shell Materia	al:
Aluminum allo	by
Shell Surface	e Treatment:
Cadmium and	d chromate
Included Cor	ntact Quantity:
21 single mat	ing end single contact grouping
Included Cor	ntact Type:
Round socket	t single mating end single contact grouping
Precious Ma	terial And Location:
Contact surfa	ces gold
Precious Ma	terial And Weight:
0.021 gold gra	ains, troy
Precious Ma	terial:
Gold	
Thread Serie	es Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	ion:
No	
Fiig:	
A039b0	
Mil-std (milit	ary Standard):
Mil-g-45204 s	spec.