## NSN 5935-00-690-9437

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-690-9437 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/cable clamp **Overall Length:** 2.700 inches **Overall Height:** 1.188 inches **Overall Width:** 1.188 inches **Unthreaded Mounting Hole Diameter:** 0.144 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Cable Entrance Diameter:** 0.875 inches **Distance From Mounting Shoulder To Front Face:** 0.670 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 24

**Thread Size:** 

0.625 inches

## NSN 5935-00-690-9437

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Contact Surface Treatment Specification:
Qq-s-365, type 2 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Surface Treatment:
Anodize
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0