

View Online at <https://aerobasegroup.com/nsn/5935-00-691-3603>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/flange

**Overall Length:**

2.020 inches

**Overall Height:**

Between 2.219 inches and 2.281 inches

**Overall Width:**

Between 2.219 inches and 2.281 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.168 inches and 0.183 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 1.745 inches and 1.755 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.745 inches and 1.755 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.875 inches and 0.906 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

32-8 all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

41.0 2nd mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 all mating ends all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 all mating ends all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

125.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

2.000 inches

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Insert Material:**

Plastic all mating ends

**Shell Material:**

Aluminum alloy

**Included Contact Quantity:**

6 1st mating end 1st contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.060 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0