NSN 5935-00-702-3732

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-702-3732 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.859 inches **Overall Diameter:** 0.500 inches **Environmental Protection:** Weatherproof **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet latch **Connector Cable Strain Relief Method:** Conduit nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.437 inches **Terminal Location:** Back single mating end single contact grouping Copper alloy single mating end single contact grouping

Contact Material: Insert Material: Plastic tetrafluoroethylene single mating end **Terminal Type:** Crimp single mating end single contact grouping

NSN 5935-00-702-3732

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0