NSN 5935-00-702-4421

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-702-4421 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.453 inches **Overall Height:** 0.859 inches **Overall Width:** 0.703 inches **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** "18, 18-20" single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket and shell Shell Type: Solid Thread Length: 0.266 inches Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Insert Material:

Plastic melamine mineral filled single mating end

NSN 5935-00-702-4421

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
18 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.018 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0