Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-702-4560



Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Angle shape, w/o cable clamp

Overall Diameter:

1.047 inches

Body Angle In Deg:

90.0

Environmental Protection:

Moisture resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

12s-3 single mating end **Contact Removability:**

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Distance From Centerline To Connector End:

2.062 inches

Distance From Centerline To Cable End:

0.984 inches

Thread Length:

0.375 inches and 0.531 inches

Thread Size:

0.625 inches and 0.750 inches

NSN 5935-00-702-4560 Electrical Plug Connector - Page 2 of 2



	ninal Location:
	k single mating end single contact grouping
	tact Material:
	per single mating end single contact grouping
	tact Surface Treatment:
	er single mating end single contact grouping
	ert Material:
	ss single mating end
	ninal Type:
	ler well single mating end single contact grouping
	II Material:
Stee	
	II Surface Treatment:
	mium
	uded Contact Quantity:
2 sir	ngle mating end single contact grouping
Incl	uded Contact Type:
Rou	nd socket single mating end single contact grouping
Pred	cious Material And Location:
Con	tact surfaces silver
Pred	cious Material And Weight:
0.00	2 silver grains, troy
Pred	cious Material:
Silve	er en
Thre	ead Series Designator:
Une	f and unef
She	If Life:
N/a	
Unit	Of Measure:
Den	nilitarization:
No	
Fiig	:
A03	9b0