

View Online at <https://aerobasegroup.com/nsn/5935-00-702-4846>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.562 inches

**Overall Diameter:**

0.938 inches

**Environmental Protection:**

Weatherproof

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

N 1st mating end

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell and internally threaded coupling ring

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Thready Qty Per Inch (tpi):**

24 and 20

**Thread Size:**

0.625 inches and 0.750 inches

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Silver all mating ends all contact groupings

**Insert Material:**

Plastic polytetrafluoroethylene all mating ends

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 all mating ends all contact groupings

**Included Contact Type:**

Coaxial socket 1st mating end single contact grouping

**Precious Material And Location:**

Contact and body surfaces silver

**Precious Material And Weight:**

0.110 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0