

View Online at <https://aerobasegroup.com/nsn/5935-00-702-6704>

**Body Style:**

Straight edge type

**Overall Length:**

Between 4.339 inches and 4.349 inches

**Overall Height:**

Between 0.427 inches and 0.447 inches

**Overall Width:**

Between 0.323 inches and 0.333 inches

**Environmental Protection:**

Shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.116 inches

**Distance Between Mounting Facility Centers:**

Between 4.026 inches and 4.036 inches

**Board Accommodated Length:**

3.583 inches single board

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Fixed contact to contact

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty sgd-f military specification single material response single mating end

**Included Contact Quantity:**

44 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.044 gold grains, troy and 0.044 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.