NSN 5935-00-702-9256

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-702-9256

| Body Style: |
|---|
| Angle shape w/cable clamp |
| Overall Diameter: |
| 1.312 inches |
| Body Angle In Deg: |
| 90.0 |
| Environmental Protection: |
| Pressure proof and heat resistant and moisture resistant and vibration resistant and watertight |
| Cable Entrance Diameter: |
| 0.438 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 27 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Distance From Centerline To Cable End: |
| 0.688 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd

Plastic silicone single mating end

Contact Surface Treatment Specification:

treatment response single mating end single contact grouping

NSN 5935-00-702-9256

Electrical Plug Connector - Page 2 of 2



| Terminal Type: |
|---|
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |
| 27 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Cable accommodated at anangle w/contact face |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.027 gold grains, troy and 0.027 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |