

View Online at https://aerobasegroup.com/nsn/5935-00-705-2967

Body Style: Straight shape Overall Length: 2.000 inches Overall Height: 0.656 inches Overall Width: 0.750 inches Distance Between Mounting Facility Centers: 1.688 inches Mating End Quantity: 1 Contact Position Arrangement Style: 34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Contact Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Maerial: Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Contact Maerial: Plastic melanine single mating end Ingle mating end single contact grouping and silver single mating end single contact grouping enter single mating end single contact grouping enter single mating end single contact grouping ente
Overall Length: 2.000 inches Overall Height: 0.656 inches Overall Width: 0.750 inches Distance Between Mounting Facility Centers: 1.688 inches Mating End Quantity: 1 Contact Position Arrangement Style: 34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Contact Naximu Gurent Rating In Amps: Jackscrew Shell Type: Solid Contact Naximu Gurent Rating In Amps: Jackscrew Shell Type: Solid Contact Nation: Jackscrew Shell Solid Contact Surface Treatment: Polarization Method: Jackscrew-Socket Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Polatic Material: Plastic melamine single mating end single contact grouping and silyer single mating end single c
2.000 inches Overall Height: 0.656 inches Overall Width: 0.750 inches Distance Between Mounting Facility Centers: 1.688 inches Mating End Quantity: 1. Contact Between Mounting Facility Centers: 3.4 single mating end Style: 3.4 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jacksrew Shell Type: Solid Connect Locking Method: Jacksrewsocket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Contact Surface Treatment: Contact Surface Treatment: Contact Surface Treatment: Contact Material: Contact Surface Treatment: Contact Surface Treatment: Contact Material: Contact Materia: Contact Materia: Contact Materia: Contact Surface Treatment: Contact Surface
Overall Height:0.656 inchesOverall Width:0.750 inchesDistance Between Mounting Facility Centers:1.688 inchesMating End Quantity:1Contact Position Arrangement Style:34 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:13.0 single mating end single contact groupingPolarization Method:JackscrewSolidConnector Locking Method:Jackscrew-socketTerminal Location:Conper alloy single mating end single contact groupingContact Maximg end single contact groupingContact Maximg In Amps:SolidConnector Locking Method:Jackscrew-socketComper alloy single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Material:Gold single mating end single contact grouping and silver single mating end single contact groupingContact Material:Partic melarine in gingle mating end single contact grouping and silver single mating end single contact groupingContact Material:Partic melarine in single mating end single contact groupingSolid rewell single mating end single contact groupingFartimal Location:Solid rewell single mating end single contact groupingContact Material:Partic melarine in single mating end single contact groupingSolid rewell single mating end single contact grouping
0.655 inches Overall Width: 0.750 inches Distance Between Mounting Facility Centers: 1.688 inches Mating End Quantity: 1 Contact Position Arrangement Style: 34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Colact Surface Treatment: Plastic melamine single contact grouping and single contact grouping Contact Surface Treatment: Plastic melamine single contact grouping and single contact grouping Insert Material: Plastic melamine single mating end single contact grouping and
Overall Width: 0.750 inches Distance Between Mounting Facility Centers: 1.688 inches Mating End Quantity: 1 Contact Position Arrangement Style: 34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Stold Contact Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Contact Surface Treatment: Plastic melamine single mating end single contact grouping Contact Surface Treatment: Plastic melamine single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end single contact grouping and silver single mating end single contact grouping and silver single mating end single contact grouping and silver single mating end single
0.750 inches Distance Between Mounting Facility Centers: 1.688 inches Mating End Quantity: 1 Contact Position Arrangement Style: 34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Contact Maximug end single contact grouping Contact Locking Method: Jackscrew Shell Type: Solid Contact Material: Gouper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic melamine single mating end Insert Material: Plastic melamine single mating end single contact grouping Lorent Material: Plastic melamine single mating end single contact grouping and silver single mating end single contact grouping enting end enting end enti
Distance Between Mounting Facility Centers: 1.688 inches Mating End Quantity: 1 Contact Position Arrangement Style: 34 single mating end Contact Removability: Norremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Method: Jackscrew-socket Farminal Location: Back single mating end single contact grouping Contact Material: Plastic metamine single mating end single contact grouping and silver single mating end single contact grouping Method: Jackscrew-socket Farminal Location: Back single mating end single contact grouping and silver single mating end single contact grouping Method: Jackscrew-socket Farminal Location: Back single mating end single contact grouping and silver single mating end single contact grouping Method: Jackscrew-socket Farminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
1.688 inches Mating End Quantity: 1 Contact Position Arrangement Style: 34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Contact Material: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Contact Surface Treatment: Polarization meting end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Imminal Location: Polarization Method: Discret Material: Polarization gen ating end single contact grouping Contact Surface Treatment: Polarization endamine single mating end Solid remain ing end single contact grouping Material: Polarization endamine single mating end single contact grouping Solder well single mating end single con
Mating End Quantity: 1 Contact Position Arrangement Style: 34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Contact Material: Dackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Contact Surface Treatment: Polarizenine single mating end single contact grouping Contact Surface Treatment: Polater metamine single mating end single contact grouping Contact Surface Treatment: Polater metamine single mating end Forminal Type: Solder well single mating end single contact grouping Surface Treatment: Polarized material: Polarized mating end single contact grouping and silver single mating end single contact grouping end single contact grouping end single contact grouping end single contact grouping end
1 Contact Position Arrangement Style: 34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Matterial: Polarization end single contact grouping and silver single mating end single contact grouping Insert Material: Polarization end single contact grouping and silver single mating end single contact grouping Insert Material: Polarization end single contact grouping and silver single mating end single contact grouping Insert Material: Polarization endaming end single contact grouping Solder well single mating end single contact grouping Hoterial: Polarization endaming end single contact grouping Solder well single mating end single contact grouping Solder well s
Contact Position Arrangement Style: 34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Contact Material: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Marriace Treatment: Polarizetion mating end single contact grouping and silver single mating end single contact grouping Insert Material: Polarizet mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Solder well single mating end single contact grouping Solder well single mating end single contact grouping Herminal Type: Solder well single mating end single contact grouping Herminal Type: Solder well single mating end single contact grouping Herminal Type: Solder well single mating end single
34 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Contact Material: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Isert Material: Plastic melamine single mating end Plastic melamine single mating end Solid Haterial: Sold single mating end single contact grouping and silver single mating end single contact grouping Contact Surface Treatment: Plastic melamine single mating end Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Ferminal Type: Solid contact Surface Treatment: Plastic melamine single mating end Insert Material: Polarization end single contact grouping Chreat Surface Treatment: Solder well single mating end single contact grouping and silver single mating end single contact grouping Chreat Surface Treatment: Solder well single mating end single contact grouping Chreat Surface Treatment: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:13.0 single mating end single contact groupingPolarization Method:JackscrewShell Type:SolidConnector Locking Method:Jackscrew-socketTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact grouping and silver single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact grouping and silver single mating end single contact groupingInsert Material:Plastic melamine single mating endSurface Treatment:Solder well single mating end single contact groupingShell Material:Aluminum alloyShell Surface Treatment:
Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Solder well single mating end single contact grouping Solder well single mating end single contact grouping Shell Material: Aluminum alloy
13.0 single mating end single contact grouping Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Single mating end single contact grouping and silver single mating end single contact grouping Forminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy
Polarization Method: Jackscrew Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Gold single mating end single contact grouping Back single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
JackscrewShell Type:SolidConnector Locking Method:Jackscrew-socketTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact grouping and silver single mating end single contact groupingGold single mating end single contact grouping and silver single mating end single contact groupingInsert Material:Plastic melamine single mating endForminal Type:Solder well single mating end single contact groupingShell Material:Auminum alloyShell Surface Treatment:
Shell Type: Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping and silver single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Ferminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Solid Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Solder well single mating end single contact grouping Solder well single mating end single contact grouping Shell Material: Aluminum alloy
Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy
Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Ferminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy
Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic melamine single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact groupingInsert Material:Plastic melamine single mating endTerminal Type:Solder well single mating end single contact groupingShell Material:Aluminum alloyShell Surface Treatment:
Insert Material: Plastic melamine single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Plastic melamine single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Shell Material: Aluminum alloy Shell Surface Treatment:
Aluminum alloy Shell Surface Treatment:
Shell Surface Treatment:
Anodize
Included Contact Quantity:
34 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping



Precious Material And Location: Contact surfaces gold and contact surfaces silver Precious Material And Weight: 0.034 gold grains, troy and 0.034 silver grains, troy Precious Material: Gold and silver Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0